This file contains an illustration of Sending Mail from within Jade

==========

Hi!

I have achieved my objective of being able to issue emails from a Jade application to an SMTP mail server.

I setup the External Function shellExecute. This is very useful as it allows you to call many Windows programs (with parameters) from within Jade e.g. Word.

Then within your jade application you can to create a temporary ASCII text file with some header information detailing who you are sending the email to, who it's from and the subject.

Here is a JadeScript that I wrote for testing it :

```
vars    tempfile: File;
begin
    create tempfile;
    tempfile.fileName := "C:\temp\TEMPMAIL.TXT";
    tempfile.kind := File.Kind_ANSI;
    tempfile.mode := File.Mode_Output;

    tempfile.writeString("Subject: Its life Jim -- but not as we know it" & CrLf);
    tempfile.writeString("From: Alan Thomson<athomson@clear.net.nz>" & CrLf);
    tempfile.writeString("To: Alan Thomson<athomson@cardinal.co.nz>" & CrLf & CrLf);
    tempfile.writeString("With reference to Complaint: 00345 raised 17 Jun 1998" & CrLf);
    tempfile.writeString("You have been assigned responsibility" & CrLf);
    tempfile.writeString("Please accept or otherwise within JACS ASAP" & CrLf);
    tempfile.writeString("." & CrLf);
    call shellExecute(1,"open","sendmail"," -messagefile=c:\temp\TEMPMAIL.TXT -t", null, 1);
end;
```